

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously Presented) An active matrix electroluminescent display device comprising an array of pixels, each pixel comprising:

an electroluminescent display element;

a drive transistor for driving a current through the display element;

a storage capacitor for storing a voltage to be used for addressing the drive transistor;

a discharge photosensitive element for discharging the storage capacitor in dependence on the light output of the display element;  
and

a further photosensitive element which is shielded from light emitted by the display element while being exposed to light from

other directions, and which is connected so as to cancel photocurrents produced in the discharge photosensitive element by light from the other directions.

2. (Previously Presented) The display device according to Claim 1, wherein the drive transistor is connected between a power supply line and the display element.

3. (Previously Presented) The display device according to Claim 2, wherein the discharge photosensitive element is connected in parallel with the storage capacitor between the power supply line and the gate of the drive transistor, and wherein the further photosensitive element is connected in series with the discharge photosensitive element between the gate of the drive transistor and a reference potential.

4. (Previously Presented) The display device according to Claim 3, wherein the reference potential is provided by a reference potential line shared by other pixels.

5. (Previously Presented) The display device according to Claim 4, wherein the pixels are arranged in rows and columns with each row of pixels having a respective row address conductor via which the row of pixels is selected in a row address phase, and wherein the pixels of a row share a respective reference potential line, and wherein the reference potential line associated with a row of pixels comprises a row address conductor associated with an adjacent row of pixels.

6. (Previously Presented) The display device according to claim 1, wherein the discharge photosensitive element and the further photosensitive element comprise photodiodes.

7. (Previously Presented) The display device according to claim 1, wherein the discharge photosensitive element and the further photosensitive element comprise diode-connected transistors.

8. (Previously Presented) The display device according to claim 1, wherein the pixel further includes an address transistor

(26) connected between an input signal line and an input to the pixel coupled to a node between the storage capacitor and the gate of the drive transistor.

9. (Previously Presented) The display device according to claim 1, wherein the device comprises a substrate, active matrix circuitry comprising the pixel drive transistors, storage capacitors and photosensitive elements overlying the substrate, and wherein the pixel display elements comprise an electroluminescent layer overlying the active matrix circuitry.

10. (Previously Presented) The display device according to Claim 9, wherein the discharge photosensitive element and the further photosensitive element in each pixel are arranged close together.

11. (Previously Presented) The display device according to Claim 9, wherein the pixel display elements include a transparent conductive electrode layer between the electroluminescent layer and the active matrix circuitry, wherein a light shield is arranged in

each pixel between the further photosensitive element and the overlying electroluminescent layer to shield the further photosensitive element from light directly from the electroluminescent layer, and wherein the discharge photosensitive element is exposed to light generated in the overlying electroluminescent layer.

12. (Previously Presented) The display device according to Claim 11, wherein the pixel display elements include a light opaque electrode layer at the side of the electroluminescent layer remote from the active matrix circuitry.

13. (Previously Presented) The display device according to Claim 11, wherein the pixel display elements include a second transparent electrode layer at the side of the electroluminescent layer remote from the active matrix circuitry, and wherein a further light shield is arranged on the second transparent electrode layer and overlying the discharge photosensitive element of a pixel.